

Wegner Automotive

N2258 Hilltop Rd.
Markesan, WI 53946
USA

"Corrected Torque and Power" from test Ring Bros.-5069.sfd

Test Information:

File name: Ring Bros.-5069.sfd (Wegner.cfa)
Data page: Corrected Torque and Power - 34 lines total
Tested on:

Test Description:

RING BROS. Coyote 3.0L Whipple inverted 8-24-26
dyno headers 112mm TB air inlet
3.700" pulley

EngSpd RPM	STPTrq Cib-ft	STPPwr CHp	Fuel_P 0-150p	Oil_P 0-150p	BoostP 0-150p	CoolOt deg F	AFR_1 ratio
4,500**	716.0	613.5	62.5	89.9	12.5	208	12.2
4,600	726.6	636.4	62.5	90.0	12.5	208	12.2
4,700	733.7	656.6	62.6	90.1	12.5	207	12.2
4,800	741.0	677.2	62.5	90.2	12.6	207	12.2
4,900	747.2	697.1	62.5	90.3	12.6	207	12.2
5,000	753.2	717.0	62.5	90.5	12.6	207	12.2
5,100	760.5	738.5	62.4	90.6	12.7	207	12.2
5,200	765.7	758.1	62.4	90.7	12.7	207	12.1
5,300	767.8	774.9	62.3	90.9	12.7	207	12.1
5,400	769.3	790.7	62.3	91.0	12.8	207	12.1
5,500	768.3	805.1	62.2	91.1	12.9	207	12.1
5,600	769.6	820.6	62.2	91.1	12.9	207	12.1
5,700	769.2	834.8	62.2	91.2	13.0	207	12.1
5,800	768.3	848.5	62.0	91.2	13.1	207	12.1
5,900	767.1	861.8	61.9	91.2	13.2	207	12.1
6,000	764.8	873.7	61.8	91.2	13.3	207	12.1
6,100	762.2	885.2	61.8	91.0	13.5	207	12.0
6,200	759.3	896.3	61.8	90.8	13.6	207	12.0
6,300	756.3	907.2	61.8	90.7	13.7	207	12.0
6,400	751.4	915.7	61.8	90.4	13.8	207	12.0
6,500	748.8	926.7	61.9	90.1	14.0	207	12.0
6,600	745.2	936.5	61.9	89.8	14.1	207	12.0
6,700	741.8	946.3	61.9	89.5	14.3	207	12.0
6,800	735.7	952.6	62.0	89.1	14.4	207	12.0
6,900	731.0	960.4	62.4	88.7	14.6	207	12.0
7,000	726.1	967.8	63.1	88.4	14.8	206	12.0
7,100	721.7	975.7	63.8	88.0	14.9	206	12.0
7,200	716.3	982.0	64.3	87.6	15.1	206	12.0
7,300	711.3	988.6	64.6	87.1	15.2	206	12.0
7,400	705.5	994.0	64.5	86.3	15.5	206	11.9
7,500	698.8	997.9	64.2	85.5	15.7	206	11.9
7,600	694.3	1,004.6	64.3	84.8	15.9	206	11.9
7,700	687.5	1,007.9	64.8	84.0	16.2	206	11.9
7,800**	679.7	1,009.5	65.4	83.3	16.4	206	11.9

Avg**

6,150 740.0 863.5 62.7 89.3 13.8 207 12.1

Min**

4,500 679.7 613.5 61.8 83.3 12.5 206 11.9

Wegner Automotive

N2258 Hilltop Rd.
Markesan, WI 53946
USA

"Corrected Torque and Power" from test Ring Bros.-5069.sfd

EngSpd RPM	STPTrq Cib-ft	STPPwr CHp	Fuel_P 0-150p	Oil_P 0-150p	BoostP 0-150p	CoolOt deg F	AFR_1 ratio
Max** 7,800	769.6	1,009.5	65.4	91.2	16.4	208	12.2